



## AIM, TRIGGER, DECODE: IT'S THAT SIMPLE!

An intuitive and effortless scanning experience is the target of the PowerScan™ 9500 series. They combine omnidirectional reading capabilities, typical in all area imaging scanners, with outstanding optical characteristics. The result is a scanner that is able to read any kind of bar code, regardless of the orientation, from contact to over 1.0 m / 3.3 ft, depending on the bar code resolution.

## MOBILITY ENHANCES PRODUCTIVITY

The PowerScan PBT9500 further enhances operator efficiency and safety with *Bluetooth®* wireless technology; no matter if you need 1 or 100 meters of freedom: you never need to worry about getting tangled up in the cable. Accurate power management allows long lasting battery life to always guarantee more than one shift of intensive scanning. Should you need to operate 24/H, a quick 3-second battery replacement combined with a single or multi-slot battery charger allows for continuous operation without interruption.

The BC9180-BT base/charger also includes in one model two different Ethernet connections: Standard Ethernet and Industrial Ethernet protocols such as Ethernet IP and Modbus.

## DEVELOPED WITH THE USER IN MIND

Handle shape, well-balanced weight and an intuitive aiming system allows high first-pass reading rates while reducing unnatural wrist movements for improved ergonomics and user comfort.

The PowerScan 9500 area imagers use a soft-pulsed white illumination light that is very gentle on the eyes and less troublesome to the operator during scan-intensive applications.

## BUILT TO LAST

The rugged mechanics of the PowerScan brand guarantees reliable, long term operation. Repeated shocks and indoor / outdoor usage in the toughest environmental conditions do not impact its performance or reliability.



### FEATURES

- High-performance Liquid Lens allows one model to read standard, wide and high density codes
- Piconet with up to 7 scanners connected to the same base station
- Snappy omnidirectional reading
- Intuitive aiming system
- Soft white light illumination
- *Bluetooth* 3.0 Compliant: Class 1
- Multiple interfaces available
- Ethernet Connectivity (Standard and Industrial)
- Lithium-Ion battery replaces in 3 seconds!
- Datalogic's Motionix™ motion-sensing technology
- Ergonomic shape
- Image capture
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Water and Particulate Sealing Rating: IP65
- In-field replaceable window and cradle contacts
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

### INDUSTRY-APPLICATIONS

- Entertainment
  - Access Control
  - Mobile Coupons
  - Ticket Validation
  - Security / Age Verification
  - Lottery
- Manufacturing Shop Floor
  - Work-in-Progress
  - Sub-Assembly
  - Component Tracking
  - Quality Control
  - Time and Cost Analysis
  - Machine Replenishment / Configuration
  - Line Inventory Control
- Warehouse and Logistic Centers
  - Shipping / Receiving
  - Parcel Preparation
  - Picking / Put Away
  - Automatic Sorting Back-Up
  - End of Line Sorting

## TECHNICAL SPECIFICATIONS

### CORDLESS COMMUNICATIONS

<b>BLUETOOTH WIRELESS TECHNOLOGY</b>	Piconet: Max. 7 readers per radio receiver (cradle and commercial dongle)
<b>PROFILES</b>	HID (Human Interface Device) SPP (Serial Port Profile)
<b>PROTOCOL</b>	Bluetooth 3.0 Certified Class 1
<b>RADIO FREQUENCY</b>	2.40 to 2.48 GHz
<b>RADIO RANGE (OPEN AIR)</b>	Class 1: Exceeds 90 m/295 ft Range distances are measured using the base station. Range with connection to other Bluetooth peripherals may show different results.
<b>SECURITY</b>	Data Encryption; Scanner Authentication

### DECODING CAPABILITY

<b>1D / LINEAR CODES</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes
<b>2D CODES</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code;
<b>POSTAL CODES</b>	Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post;
<b>STACKED CODES</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

### ELECTRICAL

<b>BATTERY</b>	Battery Type: Lithium-Ion 2150 mAh Charge Time: External Power: 4 Hours; Host Power: 10 Hours
<b>READS PER CHARGE</b>	Continuous Reading: 30,000+
<b>CRADLE INDICATOR LEDS</b>	Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)
<b>CURRENT</b>	Charging (Typical): External Power: 800 mA @ 10 VDC; POT: 500 mA @ 5 VDC
<b>OPERATING (TYPICAL) INPUT VOLTAGE</b>	150 mA @ 10 VDC External Power: 10-30 VDC; POT: 5 VDC +/- 10%

### ENVIRONMENTAL

<b>AMBIENT LIGHT</b>	0 - 100,000 lux
<b>DROP RESISTANCE</b>	Cradle: Withstands 50 drops from 1.2 m / 3.9 ft onto a concrete surface PBT9500: Withstands 50 drops from 2.0 m / 6.6 ft onto a concrete surface
<b>ESD PROTECTION (AIR DISCHARGE)</b>	20 kV
<b>HUMIDITY (NON-CONDENSING)</b>	95%
<b>PARTICULATE AND WATER SEALING</b>	IP65
<b>TEMPERATURE</b>	Operating: -20 to 50 °C / -4 to 122 °F Battery Charging: 0 to 45 °C / 32 to 113 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

### INTERFACES

<b>INTERFACES</b>	Keyboard Wedge RS-232 USB: OEM USB; USB COM; USB HID Keyboard; Optional Ethernet (Standard, Industrial)
-------------------	---

### PHYSICAL CHARACTERISTICS

<b>COLORS AVAILABLE</b>	Yellow/Black
<b>DIMENSIONS</b>	Cradle: 24.0 x 10.8 x 9.5 cm / 9.4 x 4.3 x 3.8 in PBT9500: 21.2 x 11.0 x 7.4 cm / 8.3 x 4.3 x 2.9 in PBT9500: 380.0 g / 13.4 oz
<b>WEIGHT</b>	

### READING PERFORMANCE

<b>IMAGE CAPTURE</b>	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
<b>IMAGER SENSOR</b>	PBT9530: 864 x 544; PBT9530-HP: 1280 x 1024
<b>LIGHT SOURCE</b>	Aiming: 630 - 680 nm VLD Illumination: White LEDs
<b>PRINT CONTRAST RATIO (MINIMUM)</b>	15%
<b>READING ANGLE</b>	Pitch: +/- 40°; Roll (Tilt): 360°; Skew (Yaw): +/- 40°
<b>READING INDICATORS</b>	Beeper (Adjustable Tone and Volume); Datalogic's 3GL (Three Green Lights) technology and loud beeper for good-read feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
<b>RESOLUTION (MAXIMUM)</b>	PBT9530: 1D Codes: 4 mil; 2D Codes: 7.5 mil PBT9530-HP: 1D Codes: 2.5 mil; 2D Codes: 4 mil

### READING RANGES

<b>TYPICAL DEPTH OF FIELD</b>	Minimum distance determined by symbol length and scan angle; Printing resolution, contrast, and ambient light dependent.
-------------------------------	--

PBT9530		PBT9530-HP	
4 mils	6.0 to 17.0 cm / 2.3 to 6.7 in	2.5 mils	2.0 to 6.0 cm / 0.8 to 2.3 in
7.5 mils Data Matrix	9.0 to 12.0 cm / 3.5 to 4.7 in	4 mils Data Matrix	2.0 to 6.0 cm / 0.8 to 2.3 in
10 mils Data Matrix	4.0 to 18.0 cm / 1.5 to 7.0 in	10 mils Data Matrix	2.0 to 20.0 cm / 0.8 to 7.8 in
10 mils PDF417	2.0 to 25.0 cm / 0.8 to 9.8 in	10 mils PDF417	2.0 to 30.0 cm / 0.8 to 11.8 in
13 mils	4.0 to 45.0 cm / 1.5 to 17.7 in	13 mils	3.0 to 60.0 cm / 1.1 to 23.6 in
20 mils	4.0 to 55.0 cm / 1.5 to 21.6 in	20 mils	3.0 to 70.0 cm / 1.1 to 27.5 in
40 mils	4.0 to 85.0 cm / 1.5 to 33.4 in	40 mils	3.0 to 110.0 cm / 1.1 to 43.3 in

### SAFETY & REGULATORY

<b>AGENCY APPROVALS</b>	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
<b>ENVIRONMENTAL COMPLIANCE</b>	Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H.
<b>LASER CLASSIFICATION</b>	Caution Laser Radiation - Do not stare into beam CDRH Class II: IEC 60825 Class 2
<b>LED CLASSIFICATION</b>	IEC 62471 Class 1 LED

### UTILITIES

<b>DATALOGIC ALADDIN™</b>	Datalogic Aladdin configuration program is available for download at no charge
<b>OPOS / JAVAPOS</b>	JavaPOS Utilities are available for download at no charge; OPOS Utilities are available for download at no charge
<b>REMOTE HOST DOWNLOAD</b>	Available on request

### WARRANTY

<b>WARRANTY</b>	3-Year Factory Warranty
-----------------	-------------------------

## ACCESSORIES

### Base Stations/Chargers



- BC9030-BT: Base/Charger, Multi-Interface
- BC9130-BT: Base/Dual Charger, Multi-Interface
- BC9180-BT: Base/Dual Charger, Multi-Interface/Ethernet (Standard, Industrial)

### Cases/Holsters



- HLS-P080: Universal Holster (HLS-8000)

### Mounts/Stands



- HLD-P080: Desk/Wall Holder (HLD-8000)
- 7-0404 Industrial Take-Up Reel