




4243L 42-inch LCD

Open-Frame Touchscreen



2.6" Thin



Commercial Grade



3-Year Warranty

Product Overview

The Elo Touch Solutions 4243L 42-inch full HD open-frame touchmonitor provides smooth dual-touch performance with IntelliTouch® surface acoustic wave technology. The 4243L touchmonitor is 2.6" (65 mm) in total thickness and less than 1" (25mm) in border width. The new sleek mechanical design enables thinner and smaller kiosk design for various applications like retail, hotel, gaming, transportation and other commercial users. The touch screen glass tested with robust "ball-drop" requirements supporting applications in demanding public access environments. The 4243L features a unique, injectionmolded bezel with a virtually invisible water-resistant seal, making it a good choice for the rigors of public use. Narrow borders, multiple mounting options, and a USB touch interface add to the versatility of the 4243L.

1920 x 1080 full HD provides a bright, high contrast display with wide-view angle that easily attracts and holds the user's attention

IntelliTouch surface acoustic wave technology provides dual-touch performance

LED backlighting reduces power consumption and generates less heat than traditional CCFL backlights

4243L 42" LCD Open-frame Touchmonitor

Specifications	
Model	4243L
Color	Black
Active Display Area	36.68" x 20.66" / 931.8mm x 524.8mm
Dimensions	38.49" x 22.62" x 2.56" / 977.8 mm x 574.7 mm x 65.1 mm
LCD Technology	Active matrix TFT LCD with LED backlight
Diagonal Size	42"
On-Screen Display (OSD)	<p>Accessible through switches on the unit's tethered OSD Control box.</p> <p>Controls: Menu, Up, Down, Select</p> <p>Settings: Auto Adjust (VGA Mode), Luminance, Image Setting, Color, OSD, Miscellaneous, Exit</p> <p>Luminance: Brightness, Contrast</p> <p>Image Setting: Input Select, H-Position, V-Position, Clock, Phase</p> <p>Color: Color Temperature</p> <p>OSD: Position, Timeout, Rotation, Language, Information</p> <p>Miscellaneous: Aspect Ratio, Sharpness, Recall Defaults</p> <p>Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese</p> <p>Lockouts: OSD, Power</p>
Mounting Options	VESA 4-hole mount per MIS-F, 400, 400, 6mm (side mounting brackets included with unit)
Aspect Ratio	16:9
Native Resolution	1920 x 1080
Preset Video Timings	640x480 60Hz, 720x480 60Hz, 720x576 50Hz, 800x600 56Hz, 1024x768 60Hz, 1280x720 50Hz, 1280x720 60Hz, 1280x960 60Hz, 1280x1024 60Hz, 1440x900 60Hz, 1366x768 60Hz, 1680x1050 60Hz, 1920x1080 50Hz, 1920x1080 60Hz
Number of Colors	1073 million
Brightness (typical)	LCD Panel: 500 nits; with IntelliTouch Dual-Touch: 450 nits; No Touch: 450 nits
Response Time (Tr + Tf) (typical)	8 ms
Viewing Angle (typical)	Horizontal: 89°/178°; Vertical: 89°/178°
Contrast Ratio (typical)	4000:1
Video	Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on HDMI Type A receptacle connector (ET4243L-XXWA models only); Digital DVI on Female DVI-D, Dual-Link connector (ET4243L-XXAA models only). Input Video Horizontal Sync frequency range: 31.5-75KHz, Input Video Vertical Sync (frame rate) frequency range: 47-63Hz
Power	Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz; Monitor Only - Power Consumption (Typical at 110V at 60Hz): ON: 104 W, SLEEP: 2.0 W, OFF: 0.5 W; Monitor Only - Power Consumption (Typical at 230V at 50Hz): ON: 102.0 W, SLEEP: 2.5 W, OFF: 1 W
Weight	Unpackaged: 44 lbs. (20kg) Packaged: 60.8 lbs / 27.6 kg
Shipping Dimensions	45.98" x 11.02" x 33.70" / 1168 mm x 280 mm x 856 mm
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals & Declarations	UL, FCC, cUL, IC, CB; CE; VCCI; RCM; NOM CoC; BSMI; KC, e-Standby; CCC, China RoHS, EAC
Warranty	3 year standard
MTBF	50,000 hours demonstrated
What's in the Box	QIG, OSD Remote, HDMI Cable, VGA Cable, USB Cable (Type A to B), Power Cable IEC 60320-C13 (NA plug), Power Cable IEC 60320-C13 (EU/KR plug), Power Cable IEC 60320-C13 (UK plug), Power Cable IEC 60320-C13 (AR plug), Power Cable IEC 60320-C13 (CH plug), Power Cable IEC 60320-C13 (TW plug), Power Cable IEC 60320-C13 (JP plug), Power Cable IEC 60320-C13 (NA plug), 3-pin to 2-pin, adapter for JP power cable, Side Mount Brackets x8, Side Mount Bracket Screws x16

Ordering Information

Model	Part Number	Technology	Video Interface	Interface	Surface Treatment	Availability
4243L	E000444	IntelliTouch Dual-Touch	VGA & HDMI	USB	Clear	Worldwide
	E000445	IntelliTouch Dual-Touch	VGA & DVI	USB	Clear	Asia
	E000447	No Touch	VGA & HDMI	USB	Clear	Worldwide

Accessories

Peripheral	Part Number
Cable Kit for Replacement Cables	E378229
Remote On-Screen Display (OSD)	E483757

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17051AES00084

